

Type	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			Kg
型号	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	重量
XBD3. 0/15G-DRL	420	115	195*320	4-Ø18	805	80	8-Ø18	160	208
XBD3. 2/15G-DRL	420	115	195*320	4-Ø18	805	80	8-Ø18	160	208
XBD3. 5/15G-DRL	420	115	195*320	4-Ø18	805	80	8-Ø18	160	208
XBD3. 9/15G-DRL	420	115	195*320	4-Ø18	920	80	8-Ø18	160	250
XBD4. 0/15G-DRL	420	115	195*320	4-Ø18	920	80	8-Ø18	160	250
XBD4. 2/15G-DRL	420	115	195*320	4-Ø18	1001	80	8-Ø18	160	270
XBD4. 5/15G-DRL	420	115	195*320	4-Ø18	1001	80	8-Ø18	160	270
XBD4. 7/15G-DRL	420	115	195*320	4-Ø18	1001	80	8-Ø18	160	270
XBD5. 0/15G-DRL	420	115	195*320	4-Ø18	1001	80	8-Ø18	160	280
XBD5. 2/15G-DRL	420	115	195*320	4-Ø18	1001	80	8-Ø18	160	280
XBD5. 5/15G-DRL	420	115	195*320	4-Ø18	1001	80	8-Ø18	160	280
XBD5. 6/15G-DRL	420	115	195*320	4-Ø18	1001	80	8-Ø18	160	280
XBD5. 7/15G-DRL	420	115	195*320	4-Ø18	1001	80	8-Ø18	160	280
XBD6. 0/15G-DRL	420	115	195*320	4-Ø18	1001	80	8-Ø18	160	280
XBD6. 2/15G-DRL	420	115	195*320	4-Ø18	1082	80	8-Ø18	160	280
XBD6. 5/15G-DRL	420	115	195*320	4-Ø18	1082	80	8-Ø18	160	300
XBD6. 7/15G-DRL	420	115	195*320	4-Ø18	1082	80	8-Ø18	160	300
XBD7. 0/15G-DRL	420	115	195*320	4-Ø18	1082	80	8-Ø18	160	300
XBD7. 3/15G-DRL	420	115	195*320	4-Ø18	1082	80	8-Ø18	160	300
XBD7. 5/15G-DRL	420	115	195*320	4-Ø18	1281	80	8-Ø18	160	330
XBD7. 8/15G-DRL	420	115	195*320	4-Ø18	1281	80	8-Ø18	160	330
XBD7. 9/15G-DRL	420	115	195*320	4-Ø18	1281	80	8-Ø18	160	330
XBD8. 0/15G-DRL	420	115	195*320	4-Ø18	1281	80	8-Ø18	160	330
XBD8. 3/15G-DRL	420	115	195*320	4-Ø18	1362	80	8-Ø18	160	350

Type	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			Kg
型号	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	重量
XBD8. 5/15G-DRL	420	115	195*320	4-Ø18	1362	80	8-Ø18	160	350
XBD8. 7/15G-DRL	420	115	195*320	4-Ø18	1362	80	8-Ø18	160	350
XBD9. 0/15G-DRL	420	115	195*320	4-Ø18	1392	80	8-Ø18	160	375
XBD9. 2/15G-DRL	420	115	195*320	4-Ø18	1392	80	8-Ø18	160	375
XBD9. 4/15G-DRL	420	115	195*320	4-Ø18	1392	80	8-Ø18	160	375
XBD9. 5/15G-DRL	420	115	195*320	4-Ø18	1392	80	8-Ø18	160	375
XBD9. 8/15G-DRL	420	115	195*320	4-Ø18	1392	80	8-Ø18	160	375
XBD10. 0/15G-DRL	420	115	195*320	4-Ø18	1392	80	8-Ø18	160	375
XBD10. 2/15G-DRL	420	115	195*320	4-Ø18	1473	80	8-Ø18	160	395
XBD10. 5/15G-DRL	420	115	195*320	4-Ø18	1473	80	8-Ø18	160	395
XBD10. 6/15G-DRL	420	115	195*320	4-Ø18	1473	80	8-Ø18	160	395
XBD11. 0/15G-DRL	420	115	195*320	4-Ø18	1543	80	8-Ø18	160	440
XBD11. 2/15G-DRL	420	115	195*320	4-Ø18	1543	80	8-Ø18	160	440
XBD11. 5/15G-DRL	420	115	195*320	4-Ø18	1543	80	8-Ø18	160	440
XBD11. 6/15G-DRL	420	115	195*320	4-Ø18	1543	80	8-Ø18	160	440
XBD11. 8/15G-DRL	420	115	195*320	4-Ø18	1543	80	8-Ø18	160	440
XBD11. 9/15G-DRL	420	115	195*320	4-Ø18	1543	80	8-Ø18	160	440
XBD12. 0/15G-DRL	420	115	195*320	4-Ø18	1543	80	8-Ø18	160	440
XBD12. 3/15G-DRL	420	115	195*320	4-Ø18	1624	80	8-Ø18	160	460
XBD12. 5/15G-DRL	420	115	195*320	4-Ø18	1624	80	8-Ø18	160	460
XBD12. 7/15G-DRL	420	115	195*320	4-Ø18	1624	80	8-Ø18	160	460
XBD12. 9/15G-DRL	420	115	195*320	4-Ø18	1624	80	8-Ø18	160	460
XBD13. 0/15G-DRL	420	115	195*320	4-Ø18	1624	80	8-Ø18	160	460
XBD13. 2/15G-DRL	420	115	195*320	4-Ø18	1624	80	8-Ø18	160	460

Type	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			Kg
型号	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	重量
XBD13.5/15G-DRL	420	115	195*320	4-Ø18	1624	80	8-Ø18	160	460
XBD13.7/15G-DRL	420	115	195*320	4-Ø18	1624	80	8-Ø18	160	460
XBD14.0/15G-DRL	420	115	195*320	4-Ø18	1624	80	8-Ø18	160	460
XBD14.2/15G-DRL	420	115	195*320	4-Ø18	1705	80	8-Ø18	160	480
XBD14.5/15G-DRL	420	115	195*320	4-Ø18	1705	80	8-Ø18	160	480
XBD14.7/15G-DRL	420	115	195*320	4-Ø18	1705	80	8-Ø18	160	500
XBD15.0/15G-DRL	420	115	195*320	4-Ø18	1705	80	8-Ø18	160	500
XBD15.2/15G-DRL	420	115	195*320	4-Ø18	1705	80	8-Ø18	160	500
XBD15.3/15G-DRL	420	115	195*320	4-Ø18	1705	80	8-Ø18	160	500
XBD15.5/15G-DRL	420	115	195*320	4-Ø18	1705	80	8-Ø18	160	500
XBD15.6/15G-DRL	420	115	195*320	4-Ø18	1705	80	8-Ø18	160	500
XBD16.0/15G-DRL	420	115	195*320	4-Ø18	1705	80	8-Ø18	160	500
XBD16.3/15G-DRL	420	115	195*320	4-Ø18	1786	80	8-Ø18	160	520
XBD16.5/15G-DRL	420	115	195*320	4-Ø18	1786	80	8-Ø18	160	520
XBD16.8/15G-DRL	420	115	195*320	4-Ø18	1826	80	8-Ø18	160	580
XBD17.0/15G-DRL	420	115	195*320	4-Ø18	1826	80	8-Ø18	160	580
XBD17.2/15G-DRL	420	115	195*320	4-Ø18	1826	80	8-Ø18	160	580
XBD17.5/15G-DRL	420	115	195*320	4-Ø18	1826	80	8-Ø18	160	580
XBD17.8/15G-DRL	420	115	195*320	4-Ø18	1826	80	8-Ø18	160	580
XBD18.0/15G-DRL	420	115	195*320	4-Ø18	1826	80	8-Ø18	160	580
XBD18.1/15G-DRL	420	115	195*320	4-Ø18	1907	80	8-Ø18	160	600
XBD18.2/15G-DRL	420	115	195*320	4-Ø18	2030	80	8-Ø18	160	695
XBD18.5/15G-DRL	420	115	195*320	4-Ø18	2030	80	8-Ø18	160	695
XBD18.6/15G-DRL	420	115	195*320	4-Ø18	2030	80	8-Ø18	160	695

Type	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			Kg
型号	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	重量
XBD19. 0/15G-DRL	420	115	195*320	4-Ø18	2030	80	8-Ø18	160	695
XBD19. 2/15G-DRL	420	115	195*320	4-Ø18	2030	80	8-Ø18	160	695
XBD19. 5/15G-DRL	420	115	195*320	4-Ø18	2030	80	8-Ø18	160	695
XBD19. 6/15G-DRL	420	115	195*320	4-Ø18	2030	80	8-Ø18	160	695
XBD20. 0/15G-DRL	420	115	195*320	4-Ø18	2030	80	8-Ø18	160	695