

Type	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			Kg
型号	L	H ₁	B×C	4-Ød ₁	H	DN	N-ØD ₂	ØD ₃	重量
XBD3. 0/20G-DRL	425	130	210*340	4-Ø18	1131	100	8-Ø18	180	250
XBD3. 5/20G-DRL	425	130	210*340	4-Ø18	1131	100	8-Ø18	180	250
XBD3. 7/20G-DRL	425	130	210*340	4-Ø18	1131	100	8-Ø18	180	260
XBD4. 0/20G-DRL	425	130	210*340	4-Ø18	1131	100	8-Ø18	180	260
XBD4. 2/20G-DRL	425	130	210*340	4-Ø18	1236	100	8-Ø18	180	275
XBD4. 5/20G-DRL	425	130	210*340	4-Ø18	1236	100	8-Ø18	180	275
XBD4. 8/20G-DRL	425	130	210*340	4-Ø18	1236	100	8-Ø18	180	275
XBD5. 0/20G-DRL	425	130	210*340	4-Ø18	1236	100	8-Ø18	180	275
XBD5. 1/20G-DRL	425	130	210*340	4-Ø18	1236	100	8-Ø18	180	275
XBD5. 2/20G-DRL	425	130	210*340	4-Ø18	1291	100	8-Ø18	180	305
XBD5. 5/20G-DRL	425	130	210*340	4-Ø18	1291	100	8-Ø18	180	305
XBD5. 7/20G-DRL	425	130	210*340	4-Ø18	1291	100	8-Ø18	180	305
XBD5. 8/20G-DRL	425	130	210*340	4-Ø18	1291	100	8-Ø18	180	305
XBD6. 0/20G-DRL	425	130	210*340	4-Ø18	1291	100	8-Ø18	180	305
XBD6. 4/20G-DRL	425	130	210*340	4-Ø18	1396	100	8-Ø18	180	320
XBD6. 5/20G-DRL	425	130	210*340	4-Ø18	1396	100	8-Ø18	180	320
XBD6. 8/20G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	380
XBD7. 0/20G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	380
XBD7. 5/20G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	380
XBD7. 7/20G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	380
XBD7. 8/20G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	380
XBD8. 0/20G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	380
XBD8. 5/20G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	400
XBD8. 9/20G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	400
XBD9. 0/20G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	400

Type	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			Kg
型号	L	H ₁	B×C	4-Ød ₁	H	DN	N-ØD ₂	ØD ₃	重量
XBD9. 2/20G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	400
XBD9. 5/20G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	400
XBD9. 6/20G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	400
XBD9. 8/20G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	400
XBD10. 0/20G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	400
XBD10. 2/20G-DRL	425	130	210*340	4-Ø18	1706	100	8-Ø18	180	450
XBD10. 5/20G-DRL	425	130	210*340	4-Ø18	1706	100	8-Ø18	180	450
XBD11. 0/20G-DRL	425	130	210*340	4-Ø18	1706	100	8-Ø18	180	450
XBD11. 3/20G-DRL	425	130	210*340	4-Ø18	1706	100	8-Ø18	180	470
XBD11. 5/20G-DRL	425	130	210*340	4-Ø18	1706	100	8-Ø18	180	470
XBD12. 0/20G-DRL	425	130	210*340	4-Ø18	1706	100	8-Ø18	180	470
XBD12. 1/20G-DRL	425	130	210*340	4-Ø18	1811	100	8-Ø18	180	485
XBD12. 3/20G-DRL	425	130	210*340	4-Ø18	1811	100	8-Ø18	180	485
XBD12. 5/20G-DRL	425	130	210*340	4-Ø18	1811	100	8-Ø18	180	485
XBD12. 6/20G-DRL	425	130	210*340	4-Ø18	1811	100	8-Ø18	180	485
XBD12. 8/20G-DRL	425	130	210*340	4-Ø18	1811	100	8-Ø18	180	485
XBD12. 9/20G-DRL	425	130	210*340	4-Ø18	1811	100	8-Ø18	180	485
XBD13. 0/20G-DRL	425	130	210*340	4-Ø18	1811	100	8-Ø18	180	485
XBD13. 3/20G-DRL	425	130	210*340	4-Ø18	1871	100	8-Ø18	180	520
XBD13. 5/20G-DRL	425	130	210*340	4-Ø18	1871	100	8-Ø18	180	520
XBD13. 7/20G-DRL	425	130	210*340	4-Ø18	1871	100	8-Ø18	180	520
XBD14. 0/20G-DRL	425	130	210*340	4-Ø18	1871	100	8-Ø18	180	520
XBD14. 2/20G-DRL	425	130	210*340	4-Ø18	1976	100	8-Ø18	180	540
XBD14. 5/20G-DRL	425	130	210*340	4-Ø18	1976	100	8-Ø18	180	540
XBD14. 8/20G-DRL	425	130	210*340	4-Ø18	1976	100	8-Ø18	180	540

Type	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			Kg
型号	L	H ₁	B×C	4-Ød ₁	H	DN	N-ØD ₂	ØD ₃	重量
XBD15. 0/20G-DRL	425	130	210*340	4-Ø18	1976	100	8-Ø18	180	540
XBD15. 2/20G-DRL	425	130	210*340	4-Ø18	2031	100	8-Ø18	180	630
XBD15. 5/20G-DRL	425	130	210*340	4-Ø18	2031	100	8-Ø18	180	630
XBD15. 7/20G-DRL	425	130	210*340	4-Ø18	2031	100	8-Ø18	180	630
XBD16. 0/20G-DRL	425	130	210*340	4-Ø18	2031	100	8-Ø18	180	630
XBD16. 3/20G-DRL	425	130	210*340	4-Ø18	2136	100	8-Ø18	180	650
XBD16. 5/20G-DRL	425	130	210*340	4-Ø18	2136	100	8-Ø18	180	650
XBD16. 7/20G-DRL	425	130	210*340	4-Ø18	2136	100	8-Ø18	180	650
XBD16. 8/20G-DRL	425	130	210*340	4-Ø18	2136	100	8-Ø18	180	650
XBD17. 0/20G-DRL	425	130	210*340	4-Ø18	2136	100	8-Ø18	180	650
XBD17. 3/20G-DRL	425	130	210*340	4-Ø18	2136	100	8-Ø18	180	650
XBD17. 5/20G-DRL	425	130	210*340	4-Ø18	2136	100	8-Ø18	180	650
XBD17. 8/20G-DRL	425	130	210*340	4-Ø18	2196	100	8-Ø18	180	820
XBD18. 0/20G-DRL	425	130	210*340	4-Ø18	2196	100	8-Ø18	180	820
XBD18. 3/20G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	840
XBD18. 5/20G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	840
XBD18. 8/20G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	840
XBD19. 0/20G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	840
XBD19. 3/20G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	840
XBD19. 5/20G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	840
XBD19. 8/20G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	840
XBD20. 0/20G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	840