

Type	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			Kg
型号	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	重量
XBD3. 0/25G-DRL	425	130	210*340	4-Ø18	1186	100	8-Ø18	180	260
XBD3. 5/25G-DRL	425	130	210*340	4-Ø18	1186	100	8-Ø18	180	260
XBD3. 7/25G-DRL	425	130	210*340	4-Ø18	1186	100	8-Ø18	180	260
XBD4. 0/25G-DRL	425	130	210*340	4-Ø18	1186	100	8-Ø18	180	292
XBD4. 2/25G-DRL	425	130	210*340	4-Ø18	1346	100	8-Ø18	180	310
XBD4. 5/25G-DRL	425	130	210*340	4-Ø18	1346	100	8-Ø18	180	310
XBD4. 8/25G-DRL	425	130	210*340	4-Ø18	1346	100	8-Ø18	180	310
XBD5. 0/25G-DRL	425	130	210*340	4-Ø18	1375	100	8-Ø18	180	365
XBD5. 2/25G-DRL	425	130	210*340	4-Ø18	1375	100	8-Ø18	180	365
XBD5. 5/25G-DRL	425	130	210*340	4-Ø18	1375	100	8-Ø18	180	365
XBD5. 7/25G-DRL	425	130	210*340	4-Ø18	1375	100	8-Ø18	180	365
XBD5. 8/25G-DRL	425	130	210*340	4-Ø18	1391	100	8-Ø18	180	430
XBD6. 0/25G-DRL	425	130	210*340	4-Ø18	1391	100	8-Ø18	180	430
XBD6. 3/25G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	450
XBD6. 5/25G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	450
XBD6. 7/25G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	450
XBD7. 0/25G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	450
XBD7. 2/25G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	450
XBD7. 5/25G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	450
XBD7. 8/25G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	450
XBD7. 9/25G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	469
XBD8. 0/25G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	469
XBD8. 3/25G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	489
XBD8. 5/25G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	489

XBD8. 7/25G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	489
XBD8. 8/25G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	489
XBD9. 0/25G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	489
XBD9. 2/25G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	489
XBD9. 5/25G-DRL	425	130	210*340	4-Ø18	1661	100	8-Ø18	180	555
XBD9. 8/25G-DRL	425	130	210*340	4-Ø18	1661	100	8-Ø18	180	555
XBD10. 0/25G-DRL	425	130	210*340	4-Ø18	1661	100	8-Ø18	180	555
XBD10. 2/25G-DRL	425	130	210*340	4-Ø18	1766	100	8-Ø18	180	575
XBD10. 4/25G-DRL	425	130	210*340	4-Ø18	1766	100	8-Ø18	180	575
XBD10. 5/25G-DRL	425	130	210*340	4-Ø18	1766	100	8-Ø18	180	575
XBD10. 8/25G-DRL	425	130	210*340	4-Ø18	1766	100	8-Ø18	180	575
XBD10. 9/25G-DRL	425	130	210*340	4-Ø18	1766	100	8-Ø18	180	575
XBD11. 0/25G-DRL	425	130	210*340	4-Ø18	1766	100	8-Ø18	180	575
XBD11. 2/25G-DRL	425	130	210*340	4-Ø18	1766	100	8-Ø18	180	575
XBD11. 5/25G-DRL	425	130	210*340	4-Ø18	1766	100	8-Ø18	180	575
XBD11. 8/25G-DRL	425	130	210*340	4-Ø18	1821	100	8-Ø18	180	673
XBD12. 0/25G-DRL	425	130	210*340	4-Ø18	1821	100	8-Ø18	180	673
XBD12. 3/25G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	690
XBD12. 5/25G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	690
XBD12. 8/25G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	690
XBD13. 0/25G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	690
XBD13. 1/25G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	690
XBD13. 2/25G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	690
XBD13. 5/25G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	690
XBD13. 7/25G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	690

XBD13. 8/25G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	690
XBD14. 0/25G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	690
XBD14. 2/25G-DRL	425	130	210*340	4-Ø18	2031	100	8-Ø18	180	710
XBD14. 5/25G-DRL	425	130	210*340	4-Ø18	2031	100	8-Ø18	180	710
XBD14. 8/25G-DRL	425	130	210*340	4-Ø18	2031	100	8-Ø18	180	710
XBD14. 9/25G-DRL	425	130	210*340	4-Ø18	2031	100	8-Ø18	180	710
XBD15. 0/25G-DRL	425	130	210*340	4-Ø18	2031	100	8-Ø18	180	710
XBD15. 3/25G-DRL	425	130	210*340	4-Ø18	2196	100	8-Ø18	180	907
XBD15. 5/25G-DRL	425	130	210*340	4-Ø18	2196	100	8-Ø18	180	907
XBD15. 7/25G-DRL	425	130	210*340	4-Ø18	2196	100	8-Ø18	180	907
XBD16. 0/25G-DRL	425	130	210*340	4-Ø18	2196	100	8-Ø18	180	907
XBD16. 3/25G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	925
XBD16. 5/25G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	925
XBD16. 8/25G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	925
XBD17. 0/25G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	925
XBD17. 2/25G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	925
XBD17. 5/25G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	925
XBD17. 8/25G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	925
XBD17. 9/25G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	925
XBD18. 0/25G-DRL	425	130	210*340	4-Ø18	2301	100	8-Ø18	180	925
XBD18. 3/25G-DRL	425	130	210*340	4-Ø18	2406	100	8-Ø18	180	945
XBD18. 5/25G-DRL	425	130	210*340	4-Ø18	2406	100	8-Ø18	180	945
XBD18. 8/25G-DRL	425	130	210*340	4-Ø18	2466	100	8-Ø18	180	968
XBD19. 0/25G-DRL	425	130	210*340	4-Ø18	2466	100	8-Ø18	180	968
XBD19. 2/25G-DRL	425	130	210*340	4-Ø18	2466	100	8-Ø18	180	968

XBD19. 5/25G-DRL	425	130	210*340	4-Ø18	2466	100	8-Ø18	180	968
XBD19. 8/25G-DRL	425	130	210*340	4-Ø18	2466	100	8-Ø18	180	968
XBD20. 0/25G-DRL	425	130	210*340	4-Ø18	2466	100	8-Ø18	180	968
XBD22. 0/25G-DRL	425	130	210*340	4-Ø18	2571	100	8-Ø18	180	988
XBD22. 8/25G-DRL	425	130	210*340	4-Ø18	2676	100	8-Ø18	180	1018
XBD23. 9/25G-DRL	425	130	210*340	4-Ø18	2676	100	8-Ø18	180	1018
XBD25. 0/25G-DRL	425	130	210*340	4-Ø18	2781	100	8-Ø18	180	1038