

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD3. 0/30G-DRL	425	130	210*340	4-Ø18	1131	100	8-Ø18	180	258
XBD3. 2/30G-DRL	425	130	210*340	4-Ø18	1186	100	8-Ø18	180	292
XBD3. 5/30G-DRL	425	130	210*340	4-Ø18	1186	100	8-Ø18	180	292
XBD3. 7/30G-DRL	425	130	210*340	4-Ø18	1186	100	8-Ø18	180	292
XBD4. 0/30G-DRL	425	130	210*340	4-Ø18	1186	100	8-Ø18	180	292
XBD4. 2/30G-DRL	425	130	210*340	4-Ø18	1291	100	8-Ø18	180	310
XBD4. 5/30G-DRL	425	130	210*340	4-Ø18	1291	100	8-Ø18	180	310
XBD4. 8/30G-DRL	425	130	210*340	4-Ø18	1321	100	8-Ø18	180	335
XBD5. 0/30G-DRL	425	130	210*340	4-Ø18	1391	100	8-Ø18	180	430
XBD5. 2/30G-DRL	425	130	210*340	4-Ø18	1391	100	8-Ø18	180	430
XBD5. 5/30G-DRL	425	130	210*340	4-Ø18	1391	100	8-Ø18	180	430
XBD5. 7/30G-DRL	425	130	210*340	4-Ø18	1391	100	8-Ø18	180	430
XBD6. 0/30G-DRL	425	130	210*340	4-Ø18	1391	100	8-Ø18	180	430
XBD6. 3/30G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	445
XBD6. 4/30G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	445
XBD6. 5/30G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	445
XBD6. 8/30G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	445
XBD7. 0/30G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	445
XBD7. 3/30G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	463
XBD7. 5/30G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	463
XBD7. 6/30G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	463
XBD8. 0/30G-DRL	425	130	210*340	4-Ø18	1496	100	8-Ø18	180	463
XBD8. 2/30G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	480

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD8. 4/30G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	480
XBD8. 7/30G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	480
XBD9. 0/30G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	480
XBD9. 2/30G-DRL	425	130	210*340	4-Ø18	1601	100	8-Ø18	180	555
XBD9. 5/30G-DRL	425	130	210*340	4-Ø18	1651	100	8-Ø18	180	555
XBD9. 7/30G-DRL	425	130	210*340	4-Ø18	1651	100	8-Ø18	180	555
XBD9. 8/30G-DRL	425	130	210*340	4-Ø18	1651	100	8-Ø18	180	555
XBD10. 0/30G-DRL	425	130	210*340	4-Ø18	1651	100	8-Ø18	180	555
XBD10. 2/30G-DRL	425	130	210*340	4-Ø18	1706	100	8-Ø18	180	575
XBD10. 5/30G-DRL	425	130	210*340	4-Ø18	1706	100	8-Ø18	180	575
XBD10. 8/30G-DRL	425	130	210*340	4-Ø18	1706	100	8-Ø18	180	575
XBD11. 0/30G-DRL	425	130	210*340	4-Ø18	1706	100	8-Ø18	180	575
XBD11. 3/30G-DRL	425	130	210*340	4-Ø18	1821	100	8-Ø18	180	640
XBD11. 4/30G-DRL	425	130	210*340	4-Ø18	1821	100	8-Ø18	180	640
XBD11. 5/30G-DRL	425	130	210*340	4-Ø18	1821	100	8-Ø18	180	640
XBD11. 8/30G-DRL	425	130	210*340	4-Ø18	1821	100	8-Ø18	180	640
XBD12. 0/30G-DRL	425	130	210*340	4-Ø18	1821	100	8-Ø18	180	640
XBD12. 3/30G-DRL	425	130	210*340	4-Ø18	1821	100	8-Ø18	180	640
XBD12. 4/30G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	660
XBD12. 5/30G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	660
XBD12. 8/30G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	660
XBD13. 0/30G-DRL	425	130	210*340	4-Ø18	1926	100	8-Ø18	180	660
XBD13. 2/30G-DRL	425	130	210*340	4-Ø18	1986	100	8-Ø18	180	840

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD13. 5/30G-DRL	425	130	210*340	4-Ø18	1986	100	8-Ø18	180	840
XBD13. 8/30G-DRL	425	130	210*340	4-Ø18	1986	100	8-Ø18	180	840
XBD14. 0/30G-DRL	425	130	210*340	4-Ø18	1986	100	8-Ø18	180	840
XBD14. 3/30G-DRL	425	130	210*340	4-Ø18	2091	100	8-Ø18	180	855
XBD14. 5/30G-DRL	425	130	210*340	4-Ø18	2091	100	8-Ø18	180	855
XBD14. 7/30G-DRL	425	130	210*340	4-Ø18	2091	100	8-Ø18	180	855
XBD14. 8/30G-DRL	425	130	210*340	4-Ø18	2091	100	8-Ø18	180	855
XBD15. 0/30G-DRL	425	130	210*340	4-Ø18	2091	100	8-Ø18	180	855
XBD15. 2/30G-DRL	425	130	210*340	4-Ø18	2091	100	8-Ø18	180	855
XBD15. 4/30G-DRL	425	130	210*340	4-Ø18	2091	100	8-Ø18	180	855
XBD15. 5/30G-DRL	425	130	210*340	4-Ø18	2091	100	8-Ø18	180	855
XBD15. 7/30G-DRL	425	130	210*340	4-Ø18	2091	100	8-Ø18	180	855
XBD16. 0/30G-DRL	425	130	210*340	4-Ø18	2091	100	8-Ø18	180	855
XBD16. 2/30G-DRL	425	130	210*340	4-Ø18	2196	100	8-Ø18	180	870
XBD16. 3/30G-DRL	425	130	210*340	4-Ø18	2196	100	8-Ø18	180	870
XBD16. 5/30G-DRL	425	130	210*340	4-Ø18	2196	100	8-Ø18	180	870
XBD16. 8/30G-DRL	425	130	210*340	4-Ø18	2196	100	8-Ø18	180	870
XBD17. 0/30G-DRL	425	130	210*340	4-Ø18	2196	100	8-Ø18	180	870
XBD17. 3/30G-DRL	425	130	210*340	4-Ø18	2246	100	8-Ø18	180	898
XBD17. 5/30G-DRL	425	130	210*340	4-Ø18	2246	100	8-Ø18	180	898
XBD17. 8/30G-DRL	425	130	210*340	4-Ø18	2246	100	8-Ø18	180	898
XBD17. 9/30G-DRL	425	130	210*340	4-Ø18	2246	100	8-Ø18	180	898
XBD18. 0/30G-DRL	425	130	210*340	4-Ø18	2246	100	8-Ø18	180	898

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD18. 2/30G-DRL	425	130	210*340	4-Ø18	2351	100	8-Ø18	180	1003
XBD18. 5/30G-DRL	425	130	210*340	4-Ø18	2351	100	8-Ø18	180	1003
XBD18. 6/30G-DRL	425	130	210*340	4-Ø18	2351	100	8-Ø18	180	1003
XBD18. 8/30G-DRL	425	130	210*340	4-Ø18	2351	100	8-Ø18	180	1003
XBD19. 0/30G-DRL	425	130	210*340	4-Ø18	2351	100	8-Ø18	180	1003
XBD19. 2/30G-DRL	425	130	210*340	4-Ø18	2351	100	8-Ø18	180	1003
XBD19. 4/30G-DRL	425	130	210*340	4-Ø18	2351	100	8-Ø18	180	1003
XBD19. 5/30G-DRL	425	130	210*340	4-Ø18	2351	100	8-Ø18	180	1003
XBD19. 8/30G-DRL	425	130	210*340	4-Ø18	2351	100	8-Ø18	180	1003
XBD20. 0/30G-DRL	425	130	210*340	4-Ø18	2351	100	8-Ø18	180	1003
XBD21. 1/30G-DRL	425	130	210*340	4-Ø18	2646	100	8-Ø18	180	1350
XBD21. 8/30G-DRL	425	130	210*340	4-Ø18	2646	100	8-Ø18	180	1350
XBD22. 8/30G-DRL	425	130	210*340	4-Ø18	2751	100	8-Ø18	180	1350
XBD24. 6/30G-DRL	425	130	210*340	4-Ø18	2856	100	8-Ø18	180	1350