

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD3. 0/35G-DRL	560	170	230*420	4-Ø18	1375	150	8-Ø22	240	322
XBD3. 5/35G-DRL	560	170	230*420	4-Ø18	1375	150	8-Ø22	240	322
XBD3. 8/35G-DRL	560	170	230*420	4-Ø18	1375	150	8-Ø22	240	322
XBD3. 9/35G-DRL	560	170	230*420	4-Ø18	1375	150	8-Ø22	240	322
XBD4. 0/35G-DRL	560	170	230*420	4-Ø18	1375	150	8-Ø22	240	322
XBD4. 3/35G-DRL	560	170	230*420	4-Ø18	1375	150	8-Ø22	240	322
XBD4. 5/35G-DRL	560	170	230*420	4-Ø18	1375	150	8-Ø22	240	322
XBD4. 8/35G-DRL	560	170	230*420	4-Ø18	1375	150	8-Ø22	240	322
XBD5. 0/35G-DRL	560	170	230*420	4-Ø18	1375	150	8-Ø22	240	322
XBD5. 2/35G-DRL	560	170	230*420	4-Ø18	1410	150	8-Ø22	240	391
XBD5. 5/35G-DRL	560	170	230*420	4-Ø18	1410	150	8-Ø22	240	391
XBD5. 7/35G-DRL	560	170	230*420	4-Ø18	1410	150	8-Ø22	240	391
XBD6. 0/35G-DRL	560	170	230*420	4-Ø18	1410	150	8-Ø22	240	391
XBD6. 2/35G-DRL	560	170	230*420	4-Ø18	1519	150	8-Ø22	240	411
XBD6. 5/35G-DRL	560	170	230*420	4-Ø18	1519	150	8-Ø22	240	411
XBD6. 8/35G-DRL	560	170	230*420	4-Ø18	1519	150	8-Ø22	240	411
XBD6. 9/35G-DRL	560	170	230*420	4-Ø18	1519	150	8-Ø22	240	411
XBD7. 0/35G-DRL	560	170	230*420	4-Ø18	1519	150	8-Ø22	240	411
XBD7. 2/35G-DRL	560	170	230*420	4-Ø18	1519	150	8-Ø22	240	411
XBD7. 5/35G-DRL	560	170	230*420	4-Ø18	1519	150	8-Ø22	240	411
XBD7. 8/35G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	565
XBD7. 9/35G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	565

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD8.0/35G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	565
XBD8.2/35G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	565
XBD8.5/35G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	565
XBD8.7/35G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	565
XBD9.0/35G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	565
XBD9.2/35G-DRL	560	170	230*420	4-Ø18	1743	150	8-Ø22	240	585
XBD9.5/35G-DRL	560	170	230*420	4-Ø18	1743	150	8-Ø22	240	585
XBD9.6/35G-DRL	560	170	230*420	4-Ø18	1743	150	8-Ø22	240	585
XBD9.8/35G-DRL	560	170	230*420	4-Ø18	1743	150	8-Ø22	240	585
XBD10.0/35G-DRL	560	170	230*420	4-Ø18	1743	150	8-Ø22	240	585
XBD10.3/35G-DRL	560	170	230*420	4-Ø18	1743	150	8-Ø22	240	585
XBD10.5/35G-DRL	560	170	230*420	4-Ø18	1743	150	8-Ø22	240	585
XBD10.6/35G-DRL	560	170	230*420	1803	1803	150	8-Ø22	240	761
XBD10.8/35G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	761
XBD11.0/35G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	761
XBD11.2/35G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	761
XBD11.5/35G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	761
XBD11.8/35G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	761
XBD12.0/35G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	761
XBD12.3/35G-DRL	560	170	230*420	4-Ø18	1912	150	8-Ø22	240	781
XBD12.5/35G-DRL	560	170	230*420	4-Ø18	1912	150	8-Ø22	240	781
XBD12.8/35G-DRL	560	170	230*420	4-Ø18	1912	150	8-Ø22	240	781

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD13.0/35G-DRL	560	170	230*420	4-Ø18	1912	150	8-Ø22	240	781
XBD13.2/35G-DRL	560	170	230*420	4-Ø18	1912	150	8-Ø22	240	781
XBD13.5/35G-DRL	560	170	230*420	4-Ø18	1912	150	8-Ø22	240	781
XBD13.8/35G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	804
XBD14.0/35G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	804
XBD14.2/35G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	804
XBD14.5/35G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	804
XBD14.6/35G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	804
XBD15.0/35G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	804
XBD15.2/35G-DRL	560	170	230*420	4-Ø18	2071	150	8-Ø22	240	825
XBD15.5/35G-DRL	560	170	230*420	4-Ø18	2071	150	8-Ø22	240	825
XBD15.8/35G-DRL	560	170	230*420	4-Ø18	2071	150	8-Ø22	240	825
XBD16.0/35G-DRL	560	170	230*420	4-Ø18	2071	150	8-Ø22	240	825
XBD16.2/35G-DRL	560	170	230*420	4-Ø18	2071	150	8-Ø22	240	825
XBD16.5/35G-DRL	560	170	230*420	4-Ø18	2071	150	8-Ø22	240	825
XBD16.8/35G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1155
XBD17.0/35G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1155
XBD17.2/35G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1155
XBD17.5/35G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1155
XBD17.8/35G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1155
XBD18.0/35G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1155
XBD18.2/35G-DRL	560	170	230*420	4-Ø18	2370	150	8-Ø22	240	1175

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD18.5/35G-DRL	560	170	230*420	4-Ø18	2370	150	8-Ø22	240	1175
XBD18.7/35G-DRL	560	170	230*420	4-Ø18	2370	150	8-Ø22	240	1175
XBD18.8/35G-DRL	560	170	230*420	4-Ø18	2370	150	8-Ø22	240	1175
XBD19.0/35G-DRL	560	170	230*420	4-Ø18	2370	150	8-Ø22	240	1175
XBD19.2/35G-DRL	560	170	230*420	4-Ø18	2370	150	8-Ø22	240	1175
XBD19.5/35G-DRL	560	170	230*420	4-Ø18	2370	150	8-Ø22	240	1285
XBD19.8/35G-DRL	560	170	230*420	4-Ø18	2370	150	8-Ø22	240	1285
XBD20.0/35G-DRL	560	170	230*420	4-Ø18	2370	150	8-Ø22	240	1285
XBD20.1/35G-DRL	560	170	230*420	4-Ø18	2370	150	8-Ø22	240	1285
XBD22.5/35G-DRL	560	170	230*420	4-Ø18	2479	150	8-Ø22	240	1195
XBD24.1/35G-DRL	560	170	230*420	4-Ø18	2479	150	8-Ø22	240	1195
XBD25.1/35G-DRL	560	170	230*420	4-Ø18	2588	150	8-Ø22	240	1215