

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD3.0/40G-DRL	560	170	230*420	4-Ø18	1271	150	8-Ø22	240	286
XBD3.5/40G-DRL	560	170	230*420	4-Ø18	1271	150	8-Ø22	240	286
XBD3.7/40G-DRL	560	170	230*420	4-Ø18	1271	150	8-Ø22	240	286
XBD4.0/40G-DRL	560	170	230*420	4-Ø18	1301	150	8-Ø22	240	370
XBD4.2/40G-DRL	560	170	230*420	4-Ø18	1301	150	8-Ø22	240	370
XBD4.5/40G-DRL	560	170	230*420	4-Ø18	1301	150	8-Ø22	240	370
XBD5.0/40G-DRL	560	170	230*420	4-Ø18	1301	150	8-Ø22	240	370
XBD5.5/40G-DRL	560	170	230*420	4-Ø18	1410	150	8-Ø22	240	391
XBD5.6/40G-DRL	560	170	230*420	4-Ø18	1410	150	8-Ø22	240	391
XBD6.0/40G-DRL	560	170	230*420	4-Ø18	1410	150	8-Ø22	240	391
XBD6.4/40G-DRL	560	170	230*420	4-Ø18	1569	150	8-Ø22	240	431
XBD6.5/40G-DRL	560	170	230*420	4-Ø18	1569	150	8-Ø22	240	431
XBD6.8/40G-DRL	560	170	230*420	4-Ø18	1569	150	8-Ø22	240	431
XBD7.0/40G-DRL	560	170	230*420	4-Ø18	1569	150	8-Ø22	240	431
XBD7.5/40G-DRL	560	170	230*420	4-Ø18	1569	150	8-Ø22	240	431
XBD7.8/40G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	527
XBD8.0/40G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	527
XBD8.5/40G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	527
XBD8.6/40G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	527
XBD9.0/40G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	527

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H _i	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD9.5/40G-DRL	560	170	230*420	4-Ø18	1743	150	8-Ø22	240	547
XBD9.9/40G-DRL	560	170	230*420	4-Ø18	1743	150	8-Ø22	240	547
XBD10.0/40G-DRL	560	170	230*420	4-Ø18	1743	150	8-Ø22	240	547
XBD10.5/40G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	725
XBD11.0/40G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	725
XBD11.5/40G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	725
XBD11.6/40G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	725
XBD12.0/40G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	725
XBD12.5/40G-DRL	560	170	230*420	4-Ø18	1912	150	8-Ø22	240	745
XBD13.0/40G-DRL	560	170	230*420	4-Ø18	1912	150	8-Ø22	240	745
XBD13.5/40G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	795
XBD14.0/40G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	795
XBD14.5/40G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	795
XBD15.0/40G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	795
XBD15.2/40G-DRL	560	170	230*420	4-Ø18	2071	150	8-Ø22	240	815
XBD15.5/40G-DRL	560	170	230*420	4-Ø18	2071	150	8-Ø22	240	815
XBD16.0/40G-DRL	560	170	230*420	4-Ø18	2071	150	8-Ø22	240	815
XBD16.5/40G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1140
XBD17.0/40G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1140
XBD17.5/40G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1140

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H _i	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD17.8/40G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1140
XBD18.0/40G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1140
XBD18.5/40G-DRL	560	170	230*420	4-Ø18	2480	150	8-Ø22	240	1275
XBD19.0/40G-DRL	560	170	230*420	4-Ø18	2480	150	8-Ø22	240	1275
XBD19.5/40G-DRL	560	170	230*420	4-Ø18	2480	150	8-Ø22	240	1275
XBD20.0/40G-DRL	560	170	230*420	4-Ø18	2480	150	8-Ø22	240	1275
XBD21.7/40G-DRL	560	170	230*420	4-Ø18	2589	150	8-Ø22	240	1295
XBD22.7/40G-DRL	560	170	230*420	4-Ø18	2589	150	8-Ø22	240	1295
XBD25.0/40G-DRL	560	170	230*420	4-Ø18	2698	150	8-Ø22	240	1315