

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD3.0/45G-DRL	560	170	230*420	4-Ø18	1380	150	8-Ø22	240	391
XBD3.5/45G-DRL	560	170	230*420	4-Ø18	1380	150	8-Ø22	240	391
XBD3.8/45G-DRL	560	170	230*420	4-Ø18	1380	150	8-Ø22	240	391
XBD4.0/45G-DRL	560	170	230*420	4-Ø18	1380	150	8-Ø22	240	391
XBD4.4/45G-DRL	560	170	230*420	4-Ø18	1380	150	8-Ø22	240	391
XBD4.5/45G-DRL	560	170	230*420	4-Ø18	1380	150	8-Ø22	240	391
XBD5.0/45G-DRL	560	170	230*420	4-Ø18	1430	150	8-Ø22	240	411
XBD5.5/45G-DRL	560	170	230*420	4-Ø18	1430	150	8-Ø22	240	411
XBD6.0/45G-DRL	560	170	230*420	4-Ø18	1430	150	8-Ø22	240	411
XBD6.5/45G-DRL	560	170	230*420	4-Ø18	1539	150	8-Ø22	240	442
XBD6.8/45G-DRL	560	170	230*420	4-Ø18	1539	150	8-Ø22	240	442
XBD7.0/45G-DRL	560	170	230*420	4-Ø18	1539	150	8-Ø22	240	442
XBD7.5/45G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	538
XBD7.8/45G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	538
XBD8.0/45G-DRL	560	170	230*420	4-Ø18	1634	150	8-Ø22	240	538
XBD8.5/45G-DRL	560	170	230*420	4-Ø18	1694	150	8-Ø22	240	729
XBD9.0/45G-DRL	560	170	230*420	4-Ø18	1694	150	8-Ø22	240	729
XBD9.1/45G-DRL	560	170	230*420	4-Ø18	1694	150	8-Ø22	240	729
XBD9.5/45G-DRL	560	170	230*420	4-Ø18	1694	150	8-Ø22	240	729
XBD10.0/45G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	729
XBD10.3/45G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	729
XBD10.5/45G-DRL	560	170	230*420	4-Ø18	1803	150	8-Ø22	240	729

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD11.0/45G-DRL	560	170	230*420	4-Ø18	1853	150	8-Ø22	240	752
XBD11.4/45G-DRL	560	170	230*420	4-Ø18	1853	150	8-Ø22	240	752
XBD11.5/45G-DRL	560	170	230*420	4-Ø18	1853	150	8-Ø22	240	752
XBD12.0/45G-DRL	560	170	230*420	4-Ø18	1853	150	8-Ø22	240	752
XBD12.5/45G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	802
XBD13.0/45G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	802
XBD13.5/45G-DRL	560	170	230*420	4-Ø18	1962	150	8-Ø22	240	802
XBD13.7/45G-DRL	560	170	230*420	4-Ø18	2152	150	8-Ø22	240	1117
XBD14.0/45G-DRL	560	170	230*420	4-Ø18	2152	150	8-Ø22	240	1117
XBD14.5/45G-DRL	560	170	230*420	4-Ø18	2152	150	8-Ø22	240	1117
XBD14.9/45G-DRL	560	170	230*420	4-Ø18	2152	150	8-Ø22	240	1117
XBD15.0/45G-DRL	560	170	230*420	4-Ø18	2152	150	8-Ø22	240	1117
XBD15.5/45G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1137
XBD16.0/45G-DRL	560	170	230*420	4-Ø18	2261	150	8-Ø22	240	1137
XBD16.4/45G-DRL	560	170	230*420	4-Ø18	2372	150	8-Ø22	240	1252
XBD16.5/45G-DRL	560	170	230*420	4-Ø18	2372	150	8-Ø22	240	1252
XBD17.0/45G-DRL	560	170	230*420	4-Ø18	2372	150	8-Ø22	240	1252
XBD17.5/45G-DRL	560	170	230*420	4-Ø18	2372	150	8-Ø22	240	1252
XBD18.0/45G-DRL	560	170	230*420	4-Ø18	2372	150	8-Ø22	240	1252
XBD18.5/45G-DRL	560	170	230*420	4-Ø18	2372	150	8-Ø22	240	1275
XBD19.0/45G-DRL	560	170	230*420	4-Ø18	2481	150	8-Ø22	240	1275
XBD19.5/45G-DRL	560	170	230*420	4-Ø18	2481	150	8-Ø22	240	1275

型号	外形及安装尺寸 Outline and Mounting Dimensions					进出口法兰 Inlet and outlet flange			重量
	L	H ₁	B×C	4-ØD ₁	H	DN	N-ØD ₂	ØD ₃	kg
XBD19.7/45G-DRL	560	170	230*420	4-Ø18	2481	150	8-Ø22	240	1275
XBD20.0/45G-DRL	560	170	230*420	4-Ø18	2481	150	8-Ø22	240	1275
XBD21.0/45G-DRL	560	170	230*420	4-Ø18	2481	150	8-Ø22	240	1275
XBD22.1/45G-DRL	560	170	230*420	4-Ø18	2589	150	8-Ø22	240	1295
XBD23.3/45G-DRL	560	170	230*420	4-Ø18	2589	150	8-Ø22	240	1295
XBD24.5/45G-DRL	560	170	230*420	4-Ø18	2698	150	8-Ø22	240	1315
XBD25.0/45G-DRL	560	170	230*420	4-Ø18	2698	150	8-Ø22	240	1315